



2.5INCH BLUE LEATHER DBL PALM WELDING GLOVES



WELD/2.5 BL

Description

Passion WELD/2.5 double palm protective gloves are designed for use with welding related operations. Consists of premium cow Blue split leather, with reinforced double palm for additional hand protection and a 2.5 inch wrist cuff.

Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

Specifications

Style: Gunn cut, wing thumb, double palm sewn with cotton.
 Liner: NIL
 Palm: Cow Blue lined split leather 2.1mm ± 5%
 Expect design variation, dependant on leather supplied from manufacturer. Gloves supplied either with single layer thicker hide equivalent to, 2 single layers of leather or 2 single layers equivalent to 1 layer
 Back: Cow Blue split leather 1.25mm ± 5%
 Cuff: 2.5 -inch Cow Blue split leather 1.25mm ± 5%
 Mass: ±161g Per pair

Packaging, Storage & Obsolescence

Packed 12 pairs per bundle and 60 pairs per carton for shipping. Store in a cool, dry place. Stored correctly, the gloves physical properties will not change for up to three years.



Cleaning & Maintenance

Gloves should not be left in a contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed from the gloves. Should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands.

How to decontaminate your leather glove.

Under no circumstances should leather submerged in water.

1. Prepare a lukewarm water solution using mild detergent.
2. Gently wipe your leather glove with a cloth.
3. In-order to reduce stiffening, allow the leather glove to dry naturally.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.


Size Available

Code	Size	Palm Length
WELD/6	L/10.5	125mm (±5mm)

* As per the EN420 standard, actual measurement of gloves are determined by the manufacturer, taking into account the behaviour of the glove material, its thickness (such as leather gloves, PVC gloves etc), elasticity and the intended use.

* Sizing charts only serve as a guide. Sizes and measurements are for reference only. In order to make an informed decision, always try on the gloves as each glove features a unique construction to accommodate a wearer's preferences.

Measurement Guide



Marking



129 INDUSTRIAL ROAD AMALGAM JOHANNESBURG SOUTH AFRICA

P.O.BOX 1432 CROWN MINES 2025
 www.usafety.co.za