




CHEMICAL GREEN NITRILE GLOVES



EN 388



4002X

Description

Passion ALB0050, green flock lined nitrile gloves protects the hands against many solvents and oil-based chemicals, whilst providing protection against abrasion, cuts, snags and punctures.

Reusable nitrile flock lined, chlorinated gloves. Increased length (330 mm). Protection extended beyond the wrist and over the sleeves. Excellent chemical protection and high abrasion resistance.

Suitable for use when handling chemicals in labs, cleaning and dish washing, maintenance, janitorial use, DIY use and plumbing.

Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

Compliance & Conformity

EN420:2003+A1:2009 General requirements
5: Dexterity (from 1 to 5)

EN388:2016+A1:2018 Protective gloves against mechanical Risks (Levels obtained on the palm)

4: Resistance to abrasion (from 1 to 4)

0: Resistance to cutting (from 1 to 5)

0: Resistance to tear (from 1 to 4)

2: Resistance to puncture (1 to 4)

X: Cut Resistance method (EN ISO 13997) (from A to F) Specifications

Style: Flock lined, with anti-slip patterned palm, finger and partial wrist nitrile
Liner: nitrile
Palm: 0.38 mm ± 5 %
Back: 0.38 mm ± 5 %
Cuff: open wrist cuff with pattern for ease of glove removal
Mass: 73g Per pair (size 11)


Packaging, Storage & Obsolescence

Packed 12 pairs per bundle and 120 pairs per carton for shipping. Store in a cool, dry, dark place. Stored correctly, the gloves physical properties will not change for up to three years.



Cleaning & Maintenance

Store in a cool, dry place away from frost and light in their original packaging. In case of superficial dirt: Clean with soap and water, wipe with a cloth and hang in a ventilated area to dry naturally away from any direct fire or source of heat, even for items that got wet during use.



We recommend that no bleaching or oxidizing ingredients or any fabric softeners be used.

Recommended washing temperature is between 40°C and 60°C (104~140°F) with mild detergents.

Drying temperature should not exceed 70°C (158°F). There is no remarkable impact on cut resistance during the normal life cycle of a glove, however depending on glove construction, staining and cleaning method the differences in shrinkage and colour may occur.

In order to maximize the glove life cycle, we recommend the mildest possible cleaning conditions in terms of temperature, chemicals and cycle duration.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.

Sizes Available


7-10

Code	Size	Palm Length
ALB0048	S	105mm (±2mm)
ALB0049	M	110mm (±2mm)
ALB0050	L	115mm (±2mm)
ALB0051	XL	120mm (±2mm)

**As per the EN420 standard, actual measurement of gloves are determined by the manufacturer, taking into account the behaviour of the glove material, its thickness (such as leather gloves, PVC gloves etc), elasticity and the intended use.*

**Sizing charts only serve as a guide. Sizes and measurements are for reference only. In order to make an informed decision, always try on the gloves as each glove features a unique construction to accommodate a wearer's preferences.*

Marking



Measurement Guide



129 INDUSTRIAL ROAD AMALGAM JOHANNESBURG SOUTH AFRICA

P.O.BOX 1432 CROWN MINES 2025
www.usafety.co.za